

## Panels pyramid 4,5 degrees - Mahogany without polystyrene

### Construction:

2 x 15 mm Laminated Mahogany  
Glued with waterproof adhesive

( Appr.750 kg/m<sup>3</sup> - heat conductivity: 0,13 W/mK )

### U-Value:

| U-Value - W/m <sup>2</sup> K |  |
|------------------------------|--|
| 30 mm                        |  |
| 3,50                         |  |

Heat conductivity is calculated on the basis of the practical heat conductivity of each included material - taken from data sheets and DS418, version 6, 2002. Also relating to EN 12524.

### Weight:

| Weight appr. Kg./m <sup>2</sup> |  |
|---------------------------------|--|
| 30 mm                           |  |
| 11,3                            |  |

### Measure:

Min.: 120 x 250 mm - Max.: 680 x 1200 mm

No warranty on panels larger than 400 mm in the width

### Tolerances:

Width/Height: +/- 1 mm - Diagonal: +/- 1,5 mm - Thickness: +/- 0,4 mm

### Section drawing:



|                |                 |            |
|----------------|-----------------|------------|
| Made: 07.05.14 | Data sheet: PMN | Draw.: HMN |
| Revised:       | Data sheet:     | Draw.:     |

O.H.Industri A/S  
Smedevej 17  
DK - 7430 Ikast  
+45 9725 1200  
[www.ohindustri.com](http://www.ohindustri.com)